

Better engine oils Power to perform.



TOP ANTIFREEZE BS6580

TOP ANTIFREEZE BS6580 a universal engine antifreeze, suitable for all year round usage.

PRODUCT CODE: T08051

BENEFITS

- Manufactured from pure monoethylene glycol, anti-corrosion additives and inhibitors.
- It has been specially formulated to be truly universal in its application.
- It provides a high degree of corrosion protection for all engine cooling/ antifreeze systems whether they are predominantly of aluminium or ferrous construction.
- Employs established inhibitor technology and is nitrite, amine and phosphate (NAP) free and includes borate and silicate.
- Contains a bittering agent to prevent accidental consumption.
- Suitable for all year round usage in automotive and commercial petrol and diesel engines and certain industrial applications.

Exceeds the following performance requirements:

ASTM D 3306

ASTM D 4985

SAE J 1034

BS 6580: 2010


Recommended Dilutions:

Concentration (by volume)	25%	33%	40%	50%	60%
Specific Gravity @ 20°C	1.030	1.045	1.060	1.074	1.087
Freeze Protection (°C)*	- 12	- 22	- 27	- 40	- 56

^{*}Average of freezing point and pour point.

TYPICAL ANALYSIS:







Better engine oils Power to perform.



Appearance	Clear blue liquid		
Water Content (% w/w)	4.3		
Density at 15°C (kg/l)	1.119		
Reflux Boiling Point (°C)	161		
pH (50% v/v in Deionised Water)	7.8		
Reserve Alkalinity (ml 0.1N HCl)	20.5		



