



Better engine oils

Power to protect. Power to perform.



TOP AUTO TRANS DX 6

PRODUCT CODE:TO2509

TOP DEXRON VI ATF An exceptional ATF for use in vehicles with automatic transmissions. Designed to protect your transmission through improved oxidation resistance, friction durability, shear stability and superb wear protection. Engineered using the latest additive technology to provide a consistent and responsive shift throughout the life of the oil to protect your vehicle transmissions for longer than previous Dexron type fluids.

BENEFITS:

- Enhanced additive technology for greater vehicle coverage.
- Improved anti-wear protection for extended service intervals.
- Low viscosity to reduce frictional losses through the transmission to help improve fuel economy.
- Optimised frictional characteristics that provide smooth gear shifting.
- Outstanding resistance against sludge & deposit formation.
- Superb low temperature performance.
- Exceeds the following performance criteria:

Exceeds the following performance requirements:

- Aisin Warner AW-1, AW-2, JWS 3309 (T-IV), JWS 3324 (WS)
- Allison C4
- Ford WSS-M2C922-A1, WSS-M2C924-A (XT-8-QAW)
- GM Dexron VI
- Honda Z-1 (Not CVT), DW-1
- JASO M315-2013 1-A-LV
- Mazda ATF 3317, FZ, MV
- Nissan Matic J, K, S
- ISUZU ATF WSI,
- ZF TE-ML 09, 11A, 11B, 21L ZF 5 & 6 speed transmissions
- Not suitable for vehicles with DCT or CVT transmissions

TYPICAL ANALYSIS:

Appearance		Red
Density @ 15°C (kg/m3)	ASTM D4052	0.85
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	29
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	6.0
Pour Point (°C)	ASTM D97	-43
Viscosity Index	ASTM D2207	160

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie

