

Better engine oils 🔫 Power to protect. Power to perform.



TOP CHF PLUS

PRODUCT CODE: TO2900

TOP CHF PLUS A carefully formulated synthetic fluid designed to provide high performance in a wide range of operating conditions to a variety of essential automotive systems including power steering, self-levelling hydropneumatic suspension, shock absorbers, traction and stability control, hydraulics for convertible tops and central locking systems.

BENEFITS:

- Exceptionally high viscosity index to give performance over a wide temperature range.
- Excellent corrosion resistance.
- Outstanding anti-wear & anti-oxidant properties.
- Provides excellent lubricity.
- Superb hydrolytic stability.

Exceeds the following performance requirements:

- BMW 81 22 9 407 758
- ISO 7308
- MAN 3623/93
- Mercedes-Benz 345.0
- Opel B040.0070
- Porsche 000.043.203.33
- VW/Audi G 002 000 A2/TL 52 146

TYPICAL TEST ANALYSIS:

Appearance	Clear green fluid	
Density @ 15°C (kg/m3)	ASTM D4052	0.835
Flash Point (°C)	ASTM D92	>130
Kinematic Viscosity @ 40°C (mm/s²)	ASTM D445	18.7
Kinematic Viscosity @ 100°C (mm/s²)	ASTM D445	6
Operating Temperatures Range	-40°C to 130°C	
Pour Point (°C)	ASTM D97	<-50
Viscosity Index	ASTM D2207	310