



Better engine oils

Power to protect. Power to perform.



TOP CVT FLUID (Green)

PRODUCT CODE: TO2455

TOP CVT FLUID CVT Fluid combines synthetic base stocks and advanced additive technology that work synergistically to offer high levels of anti-wear, anti-foam and highly resistant to degradation. Specifically designed for use with the new generation of continuous variable transmissions systems that are either belt or chain driven.

BENEFITS:

- Compatible with most seals & materials.
- Durable anti-shudder for consistent performance.
- Enhanced shear stability maintains effective lubrication.
- Excellent foam control. Maintains constant frictional performance.
- Multi-vehicle & compatible with most hybrid CVT transmissions.
- Optimises fuel efficiency & low temperature fluidity.
- Superb oxidation & thermal stability.

Exceeds the following performance requirements:

- BMW 83 22 0 136 376, 83 22 0 429 154
- Chrysler, Jeep, Dodge NS-2, CVT +4
- GM DEX CVT
- Honda HMMF*, HCF 2, Z-1*, CVT*, Ultra HEVF-Type 1
- Hyundai/Kia SP-III (CVT models)
- Mazda JWS 3320
- MG Rover EM-CVT
- Mini Cooper EZL 799A
- Mitsubishi SP-III (CVT only)
- Nissan NS-1, 2, 2V, 3, N-CVT
- Renault CVT CK/SK/FK
- Subaru High Torque CVTF-LV
- Toyota CVTF TC, CVTF FE, THSII
- Volvo CVT 4959
- VW/Audi TL 521 80 (G052 180), TL 521 16 (G052 516) Do not use in DCT applications. *Not suitable for applications with starting clutch.
- Mitsubishi CVTF-J1, CVTF-J4/J4+, CVTF ECO J4,
- Mini Cooper EZL 799/EZL 799A/ZF CVT V1
- Opel/Vauxhall 7-speed CVT (95529854)
- Perodua D-CVT
- PSA 9735EF
- Fujijyuuko i-CVTF FG
- GM/Saturn CVTF I-Green 2
- Honda e:HEV, iMMD
- Hyundai/Kia CVT-1

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie



JASO



Better engine oils



Power to protect. Power to perform.



- Idemitsu CVTF-EX1
- Jatco CVT 8 Hybrid
- Lexus Fluid TC, FE
- Chery CVT
- Daihatsu CVTF DFE, DC, DFD, TC
- Fiat Tuteka CVT N.G
- Ford Escape Hybrid eCVT
- Punch CVTF-EX1
- Subaru iCVT, ICVT FG, eCVT
- Suzuki CVTF 3320, 4401, NS-2
- Zotye CVT

TYPICAL ANALYSIS:

Appearance Green Density @ 15°C (kg/m3)	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>180
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	38
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	7.6
Pour Point (°C)	ASTM D97	<-40
Viscosity Index	ASTM D2207	173

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie



JASO