

## Better engine oils Power to perform.



## TOP COOLANT XLL RED

**PRODUCT CODE: T06939** 

**TOP COOLANT XLL RED** is an ethylene glycol based engine coolant concentrate, which uses Organic Acid Inhibitor Technology and is free from nitrites, amines, phosphates, borates and silicates. It is BTC Classification Type 4E.

## **BENEFITS**

- Application: suitable for all year round usage in automotive and commercial petrol and diesel engines and certain industrial applications.
- Fleet trials have shown that when used at the correct concentration coolants based on Organic Acid Inhibitor Technology continue to provide effective corrosion protection for up to 250,000km for passenger cars and 500,000km in commercial vehicles.
- It is recommended that the coolant is replaced when the above mileages have been reached or after 5 years. provides excellent protection to engine cooling systems, whether they are predominantly of ferrous or aluminium construction.
- Unlike traditional coolants which employ inorganic inhibitors, has excellent hard water stability and very low inhibitor depletion rates.
- Exceeds the following performance requirements:
- ASTM D 3306
- ASTM D 4985
- SAE J 1034
- BS 6580: 2010
- JIS K 2234 \*
- AFNOR NF R15-601 \*
- FFV Heft R443
- CUNA NC 956-16
- UNE 26361-88
- NATO S 759
- Volvo VCS Coolant
- Chrysler MS 9176
- Cummins 85T8-2 & 90T8-4
- Leyland Trucks LTS 22 AF 10







## Better engine oils Power to protect. Power to perform.



- Mack 014GS 17004
- MAN 248, 324 (SNF) & B&W D 36 5600
- Mercedes MB 325.3
- Renault 41-01-001
- VAG TL 774 D/F, **G12, G12+**
- GM 1899 M, US 6277 M & OPEL GM QL130100
- John Deere H 24 B1 & C1
- MTU MTL 5048
- Ford ESE M97B49-A, WSS-M97B44-D, WSS-M97B44-C & ESD M97B49-
- can be used where Glysantin®, G30, G33 or G34 were originally recommended.



