



# Better engine oils

Power to protect. Power to perform.



## TOP EP LUBRICANT SY 320

**PRODUCT CODE: TO281220**

**TOP EP LUBRICANT SY 220** A range of high-performance synthetic PAO industrial gear oils synergistically blended with extreme pressure anti-wear technology. The SYN-HC range is designed to provide exceptional oxidation and corrosion protection in industrial gearbox's that operate in arduous high load conditions.

### BENEFITS:

- Compatible with seals and metals containing copper.
- Excellent low temperature performance.
- Extended lubricant life between oil changes.
- High viscosity index for applications requiring a wide temperature range.
- Lower coefficient of friction than mineral oils resulting in reduced operation costs.
- Superb high temperature stability and low volatility resulting in reduced oil consumption.

Exceeds the following performance requirements:

- AGMA 9005-E02: 252.04
- David Brown S1.53.101
- DIN 51517 Part III
- US Steel 224

### TYPICAL ANALYSIS:

Density @ 15°C (kg/m3)	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )	ASTM D445	320
Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> )	ASTM D445	36.5
Pour Point (°C)	ASTM D97	<-40
Viscosity Index	ASTM D2207	162

Northwest Business Park Collooney, Co Sligo, Ireland  
Tel: 071-9130033 Email: Info@Falzol.ie



JASO