



Better engine oils

Power to protect. Power to perform.



TOP GEAR LS 80W-90

PRODUCT CODE: TO2331

TOP GEAR LS 80W-90 Specially formulated extreme pressure gear oils FOR USE IN LIMITED SLIP DIFFERENTIALS. The introduction of the limited slip differential introduced further requirements for lubricants. The use of multipurpose gear oils did not prevent the chatter and slip stick operation of the clutches. Manufactured from high quality base oils, performance EP additives and specially selected friction modifiers to provide lubricants with the exacting requirements for limited slip operations.

BENEFITS:

- Reduces whining and chattering
- Excellent high temperature stability
- Ensures clutches slide smoothly
- Extreme pressure properties

Suitable for limited slip differentials fitted to cars, vans, trucks, buses, and agricultural and construction equipment.

Exceeds the following performance requirements:

- API GL-5 LS
- Military-L-2105B
- ZF TE-ML 05C, 21C

TYPICAL ANALYSIS:

SAE Viscosity	90
Product Code	
Appearance	Amber
Specific Gravity @ 15.6°C	0.888
Kinematic Viscosity @ 100°C (cSt)	17.59
Kinematic Viscosity @ 40°C (cSt)	194.13
Viscosity Index	98
Flash Point COC (°C)	219
Pour Point (°C)	-19