



Better engine oils

Power to protect. Power to perform.



TOP GEAR MP 85W-140

PRODUCT CODE: TO2314

TOP GEAR MP 85W-140 is an universal high performance mineral MP gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-140 GL-5 is been required. Is formulated with high refined mineral base stocks in combination with a special MP-additive technology to achieve the following performance:

BENEFITS:

- Very good protection against wear.
- Very good performance against the forming of foam and corrosion.
- Good Oxidation- and thermal stability.

Exceeds the following performance requirements:

- API GL-5 MIL-L-2105D

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	85W-140
Density @15°C	kg/m ³	ASTM D4052	910
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	421
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	29.1
Viscosity Index		ASTM D2270	96
Viscosity Brookfield @-12°C	cP	ASTM D5293	<150000
Flash Point COC, min	°C	ASTM D92	>210
Pour Point	°C	ASTM D97	-15