

Better engine oils Power to protect. Power to perform.



TOP GEAR OIL LSP 80W90

PRODUCT CODE:

TOP GEAR OIL LSP 80W90 is an API GL-5 gear oil with special 'limited slip' inhibitors for hypoid drives and limited slip differentials. Meeting the 2000 ppm phosphorus limit as required for Liebherr. Contains additives for an optimum protection under heavy duty operating conditions and heavy shock loads. Because of the special friction characteristics, squeaking and/or vibrations are avoided. Moreover, the product has an excellent low temperature fluidity for an optimum performance during all seasons.

BENEFITS:

- Offers an excellent stability against oxidation and ageing; seals are not affected by this product.
- Special friction modifiers make this oil suitable for limited slip differentials, also if equipped with multi-disc clutches, in passenger cars, commercial vehicles, tractors and earthmoving equipment.
- The undesirable noise when taking a turn, is being avoided by using this lubricant.

Exceeds the following performance requirements:

- Is recommended for hypoid drives, hub reductions, (transfer) gearboxes, PTO's and differentials where an API GL-5 and/or MIL-L-2105-D specification is prescribed.
- API GL-5
- MIL-L-2105D
- Liebherr
- ZF TE-ML 05C/12C/16E/21C
- New Holland-520B

TYPICAL ANALYSIS:

Colour		brown
Density at 20°C	0.898 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	141.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.5 cSt	ASTM D 445
Viscosity Index	102	ASTM D 2270
Flash point	212 °C	ASTM D 93
Pour point	-24 °C	ASTM D 97
Brookfield Viscosity	144000 mPa.s	ASTM D 2983

Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Info@Falzol.ie







Better engine oils





Power to protect. Power to perform.

Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Info@Falzol.ie



