

Better engine oils Power to protect. Power to perform.



TOP HT FLUID TO-4 50

PRODUCT CODE: TO2550

TOP HT FLUID TO-4 50 is specifically designed for powershift transmissions, final drives and wet brakes on heavy duty off-highway equipment used in earthmoving, mining logging, road transport and agricultural applications. Formulated with high refined solvent mineral base stock in combination with a special additive package to reach the following properties.

BENEFITS:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing

Exceeds the following performance criteria:

- CATERPILLAR TO-4
- KOMATSU KES 07.868.1
- TREMAC/ TTC
- API CF-2/CF

TYPICAL ANALYSIS:

| Properties | Unit | Method | Typical Value |
|-----------------------|--------------------|------------|---------------|
| | | | |
| SAE Grade | | SAE J300 | 50 |
| Density @15°C | kg/m ³ | ASTM D4052 | 900 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 210 |
| Kin. Viscosity @100°C | mm²/s | ASTM D7042 | 18.1 |
| Viscosity Index | | ASTM D2270 | 96 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -15 |
| Total Base Number | mgKOH/g | ASTM D2896 | 7.6 |



