

Better engine oils Power to protect. Power to perform.



TOP HT FLUID WB

PRODUCT CODE: TO2503

TOP HT FLUID WB is a fully synthetic, low viscosity universal tractor transmission oil designed to provide long drain performance in a wide variety of off-highway applications. It is suitable for many modern tractor transmissions, hydraulics, final drives and wet brake systems. Can also be used in older equipment and in particular where any of the following industry or OEM specifications are required.

BENEFITS:

- Improved anti-squawk performance in brake systems
- Excellent oxidation stability
- Outstanding anti-wear protection
- Meets the very latest OEM requirements
- Excellent low temperature properties

EXCEEDS THE FOLLOWING PERFORMANCE REQUIREMENTS:

- API GL-4,
- VOLVO WB 102 (97304), WB 101 (97303),
- JOHN DEERE J20D, J20C, J20B, J20A,
- MASSEY FERGUSON M1145, M1143, M1141, M1135,
- CASE NEW HOLLAND MAT 3540, MAT 3526, MAT 3525, MAT 3505,
- CASE MS 1206, MS 1207, MS 1209, MS 1210,
- NEW HOLLAND NH 420A, NH 410B,
- ZF TE-ML 03E / 05F / 06K / 17E / 21F
- CLAAS AGRISHIFT GA 12
- WB REN GIMA1145 80W
- KUBOTA SUPER UDT, UDT,
- VALTRA G2-08,
- ALLISON C-4,
- CATERPILLAR TO-2,
- FORD M2C134-D, M2C86-B,
- KOMATSU AXO80

TYPICAL ANALYSIS:







Better engine oils Power to protect. Power to perform.





Appearance	Clear and Bright
Density @ 15.6°C	0.858
Kinematic Viscosity @ 100°C (cSt)	7.80
Kinematic Viscosity @ 40°C (cSt)	39.8
Viscosity Index	171
Brookfield Viscosity @ -40°C (cP)	20,300
Flash Point COC (°C)	225
Pour Point (°C)	-48



