

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 24-2-2015

Revision date: 14-3-2016

Supersedes:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Top HT Fluid WB (TO2503200)
Product code : TO2503200
Type of product : Lubricant
Product group : Lubricant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Lubricant
Industrial/Professional use spec : Industrial
For professional use only
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Derfal Limited,
North West Business Park,
Collooney, Co. Sligo, F91PPT0
Ireland
Ph: 0719130033
<https://falzol.ie/>

1.4. Emergency telephone number

Emergency number

Country	Organisation/Company	Address	Emergency number	Comment
Iceland	Eitrunarmiðstöð Landspítali	Fossvogi 108 Reykjavik	+354 543 22 22	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 '+353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	+356 2545 6504	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2 H319 Calculation method

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H319 - Causes serious eye irritation

Precautionary statements (CLP) :

P264 - Wash Skin thoroughly after handling
P280 - Wear protective gloves, eye protection, face protection
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention

2.3. Other hazards

Other hazards not contributing to the classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (Note L)	(CAS No) 64742-54-7 (EC no) 265-157-1 (EC index no) 649-467-00-8 (REACH-no) 01-2119484627-25	>= 75	Asp. Tox. 1, H304
Lubricating oils, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] substance with a Community workplace exposure limit (Note L)	(CAS No) 74869-22-0 (EC no) 278-012-2 (EC index no) 649-484-00-0	1 - 5	Not classified
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	(CAS No) 68649-42-3 (EC no) 272-028-3 (REACH-no) 01-2119657973-23	0,5 - 5	Eye Dam. 1, H318 Aquatic Chronic 2, H411
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate substance with a Community workplace exposure limit (Note D)	(CAS No) 80-62-6 (EC no) 201-297-1 (EC index no) 607-035-00-6 (REACH-no) 01-2119452498-28	< 0,1	Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Assure fresh air breathing. Allow the victim to rest.

First-aid measures after skin contact : Wash skin with plenty of water. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get immediate medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : After adequate first aid, no further treatment is required unless symptoms reappear.

Symptoms/injuries after inhalation : After adequate first aid, no further treatment is required unless symptoms reappear.

Symptoms/injuries after skin contact : After adequate first aid, no further treatment is required unless symptoms reappear.

Symptoms/injuries after eye contact : After adequate first aid, no further treatment is required unless symptoms reappear. Causes serious eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Eliminate all ignition sources if safe to do so.
Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage temperature : 45 °C
Storage area : Store away from heat. Store in a well-ventilated place.
Special rules on packaging : Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Lubricating oils, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] (74869-22-0)		
EU	IOELV TWA (mg/m ³)	5 mg/m ³
EU	IOELV STEL (mg/m ³)	10 mg/m ³
Belgium	Limit value (mg/m ³)	5 mg/m ³ 8 Hrs
Belgium	Short time value (mg/m ³)	10 mg/m ³ 15 Min
Bulgaria	OEL TWA (mg/m ³)	5 mg/m ³ 8 Hrs
Czech Republic	Expoziční limity (PEL) (mg/m ³)	10 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	5 mg/m ³ 8 Hrs
Denmark	Grænseværdie (kortvarig) (mg/m ³)	1 mg/m ³
Finland	HTP-arvo (15 min)	5 mg/m ³ 8 Hrs
Greece	OEL TWA (mg/m ³)	5 mg/m ³ 8 Hrs
Hungary	CK-érték	5 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	5 mg/m ³ 8 Hrs
Latvia	OEL TWA (mg/m ³)	5 mg/m ³ 8 Hrs
Lithuania	IPRV (mg/m ³)	1 mg/m ³ 8 Hrs
Lithuania	TPRV (mg/m ³)	3 mg/m ³ 15 Min
Netherlands	Grenswaarde TGG 8H (mg/m ³)	5 mg/m ³ 8 Hrs
Portugal	OEL TWA (mg/m ³)	5 mg/m ³ 8 Hrs
Portugal	OEL STEL (mg/m ³)	10 mg/m ³
Romania	OEL TWA (mg/m ³)	5 mg/m ³ 8 Hrs
Romania	OEL STEL (mg/m ³)	10 mg/m ³ 15 Min
Slovakia	NPHV (priemerná) (mg/m ³)	5 mg/m ³ 8 Hrs
Spain	VLA-ED (mg/m ³)	5 mg/m ³ 8 Hrs
Spain	VLA-EC (mg/m ³)	10 mg/m ³ 15 Min
Sweden	nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³
Sweden	kortidsvärde (KTV) (mg/m ³)	3 mg/m ³
United Kingdom	WEL TWA (mg/m ³)	500 mg/m ³
Norway	Grenseverdier (AN) (mg/m ³)	1 mg/m ³
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
methyl methacrylate, methyl 2-methylprop-2-enoate, methyl 2-methylpropenoate (80-62-6)		
EU	Local name	Methyl methacrylate
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (ppm)	100 ppm
Netherlands	Local name	Methylmethacrylaat
Netherlands	Grenswaarde TGG 8H (mg/m ³)	205 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	410 mg/m ³
Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)		
EU	IOELV TWA (mg/m ³)	5 mg/m ³
Belgium	Limit value (mg/m ³)	5 mg/m ³
USA - ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA - ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid.
- Personal protective equipment : Gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Materials for protective clothing : Wear suitable protective clothing
Hand protection : Breakthrough time : refer to the recommendations of the supplier

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes)	0.7	3 (> 0.65)	EN 374
	Polyvinylchloride (PVC)	2 (> 30 minutes)	0.4	3 (> 0.65)	EN 374

Eye protection : Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. EN 166

Skin and body protection : Avoid prolonged and repeated contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

Respiratory protection : Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Particle filter. EN 143



Environmental exposure controls : Avoid release to the environment.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Characteristics.
Colour : Brown.
Odour : Characteristics.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : Not applicable
Freezing point : -35 °C
Boiling point : No data available
Flash point : > 210 °C
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Non flammable
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Density : 859,6 kg/m³
Solubility : insoluble in water.
Log Pow : No data available
Viscosity, kinematic : 51,1 cSt @40°C
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

Other properties : See Product Data Sheet for detailed information.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

LD50 oral (rat) 3100 mg/kg

LD50 dermal (rat) > 2000 mg/kg

Lubricating oils, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] (74869-22-0)

LD50 oral (rat) > 5000 mg/kg

LD50 dermal (rabbit) > 5000 mg/kg

LC50 inhalation (rat) (Vapours - mg/l/4h) > 5000 mg/l/4h

Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral > 5000 mg/kg

LD50 dermal (rabbit) > 2000 mg/kg

Skin corrosion/irritation : Not classified

Additional information : Based on available data, the classification criteria are not met

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : Not classified

Additional information : Based on available data, the classification criteria are not met

Specific target organ toxicity (repeated exposure) : Not classified

Additional information : Based on available data, the classification criteria are not met

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

7895 - Universal Tractor Power Syn 80W

Viscosity, kinematic 51,1 mm²/s @40°C

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
LC50 fish 1	35 (≥ 1) mg/l
EC50 Daphnia 1	1,5 mg/l
Lubricating oils, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] (74869-22-0)	
LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h algae (1)	100 mg/l
NOEC chronic crustacea	10 mg/l 21 d
Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)	
EC50 Daphnia 1	10000 mg/l

12.2. Persistence and degradability

7895 - Universal Tractor Power Syn 80W	
Persistence and degradability	Not established.
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
Persistence and degradability	Not readily biodegradable.
Lubricating oils, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] (74869-22-0)	
Biodegradation	31 % 28 Days OECD TG 301 B

12.3. Bioaccumulative potential

7895 - Universal Tractor Power Syn 80W	
Bioaccumulative potential	Not established.
Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)	
Log Kow	> 4

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations : Dispose of contents/container to an approved waste disposal plant, See Directive 2001/118/EC. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4)

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Ministry's list of carcinogens : Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts, Lubricating oils, Baseoil - unspecified, [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.], Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] are listed

Ministry's list of mutagens : Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts, Distillates (petroleum), hydrotreated heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] are listed

NON-exhaustive list of reproductive toxins - Breastfeeding : None of the components are listed

NON-exhaustive list of reproductive toxins - Fertility : None of the components are listed

NON-exhaustive list of reproductive toxins - Evolution : None of the components are listed

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
PBT	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rai
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Top HT Fluid WB (TO2503200)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H411	Toxic to aquatic life with long lasting effects

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness