



Better engine oils

Power to protect. Power to perform.



TOP HYDROL H 15

PRODUCT CODE: T03504

TOP HYDROL AW 15 is a universal mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application. Formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

BENEFITS:

- Excellent stability against oxidation.
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.

Exceeds the following performance criteria:

- AFNOR NFE 48-603
- ISO 11158 HM
- DIN 51524/2 HLP

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	15
Density @15°C	kg/m ³	ASTM D4052	864
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	15
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	3.5
Viscosity Index		ASTM D2270	98
Flash Point COC, min	°C	ASTM D92	180
Pour Point	°C	ASTM D97	-39
Air Release Value @50°C	Minutes	DIN 51381	Pass
Demulsibility @54°C	Minutes	DIN 51599	Pass

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie



JASO