



# Better engine oils

Power to protect. Power to perform.



## TOP HYDROL HVI 15

**PRODUCT CODE: TO3604**

**TOP HYDROL HVI 15** Premium high viscosity index industrial hydraulic oils. Manufactured from a blend of solvent refined mineral oils, viscosity index improver and a multipurpose hydraulic oil additive system. Exhibit excellent oxidation resistance lowering the possibility of gums and lacquers. Is engineered to maintain viscosity control over wide temperature in a range of different applications.

### BENEFITS:

- Outstanding anti-wear, anti-oxidant and anti-foam additives.
- High performance and smooth hydraulic operations.
- Excellent water separating characteristics to minimize emulsions.
- Thermal stability minimizes sludge deposits and viscosity increase due to oxidation.
- The high viscosity index additive system to give high performance over a wide temperature range. The primary applications for HVI hydraulic oils are hydraulic systems that require a uniform hydraulic oil viscosity over a wide temperature range, including machinery operating under very high pressures, with vane pumps.

### TYPICAL ANALYSIS:

Density @ 15°C	-	0.85	<b>Denison</b>	HF-0, 2
Flash Point (°C)	-	>130	<b>DIN 51524</b>	Part 3
Kinematic Viscosity @ 40°C (cSt)	-	15	<b>ISO 6743-4</b>	Type HV
Kinematic Viscosity @ 100°C (cSt)	-	3.81	<b>ISO 11158</b>	Type HV
Pour Point (°C)	-	-36		
Viscosity Index	-	150		