



Better engine oils

Power to protect. Power to perform.



TOP LHM FLUID

PRODUCT CODE:

TOP LHM FLUID LHM Fluid is manufactured from specialised mineral oil and selected additive technology to produce a hydraulic and brake fluid with a very high viscosity index. Specifically designed for use in Citroen vehicles with hydro-pneumatic suspension and brakes. This grade is designed to protect against pump wear and provide good rates of flow throughout the system even in arduous conditions.

BENEFITS:

- Excellent corrosion resistance.
- Outstanding anti-wear & anti-oxidant properties.
- Provides excellent lubricity.
- Suitable for use in systems with pressure up to and in excess of 150bar.
- Superb hydrolytic stability.
- Very high viscosity index to give performance over a wide temperature range.

Exceeds the following performance requirements:

- Fiat 9.55597
- Ford ESN-M6C59A
- ISO 7308
- PSA B71 2710
- Suitable to use as a mineral hydraulic fluid in Audi, Citroen and certain Jaguar applications or systems using green mineral oil.

TYPICAL ANALYSIS:

Appearance		Clear & bright green fluid
Density @ 15°C (kg/m ³)	ASTM D4052	0.84
Flash Point (°C)	ASTM D92	>130
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	17
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	6.1
Pour Point (°C)	ASTM D97	<-50
Viscosity Index	ASTM D2207	350