



Better engine oils

Power to protect. Power to perform.



TOP MHF FLUID

TOP MHF FLUID A mineral hydraulic fluid, specially developed for Level control system, hydropneumatic suspension, hydraulic system from ASD, 4MATIC and soft top (convertible top) in certain Mercedes-Benz passenger cars.

BENEFITS:

- Ensures a superiour wear protection as well as excellent fluidity, even at very low temperatures. Shows dedicated friction characteristics and offers adequate protection against corrosion and alteration.
- Formulated for applications (levelling systems, shock absorbers and power steering) where the MB 343.0 specification is prescribed.
- Ensures a good working hydraulic system under all circumstances in particular because of the excellent damping characteristics.
- Although a miscible with most of the conventional hydraulic fluids, mixing is discouraged in order to benefit of the unique properties.

Exceeds the following performance requirements:

- MB 343.0
- DIN 51524/3 (HVLP) ISO 7308

TYPICAL ANALYSIS:

| | | |
|-------------------------------|------------|-------------|
| Colour | Yellow | |
| Density at 20°C | 0.865 kg/l | ASTM D 1298 |
| Viscosity, kinematic at 40°C | 20 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 6.2 cSt | ASTM D 445 |
| Viscosity Index | 280 | ASTM D 2270 |
| Flash point | 100 °C | ASTM D 93 |
| Pour point | -51 °C | ASTM D 97 |

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie



JASO