

## Better engine oils Power to protect. Power to perform.



## **TOP MTF 75W 80**

**PRODUCT CODE: T07021** 

**TOP MTF 75W 80** a synthetic Long Life Multi MTF. This product has been specially developed for use in modern manual transmissions in cars and vans. New generation advanced additives and synthetic base oils.

#### **BENEFITS:**

- Smooth and easy gear-changing at both low and high operating temperatures.
- Outstanding oxidation stability: long service life and long-term resistance to high operating temperatures.
- Synchromeshes are able to operate as smoothly as possible 'problem-free' gear-changing and optimal protection against wear under extreme operating conditions, due to special EP additives.
- Outstanding resistance to corrosion and foam formation.
- a special SAE 75W-80 manual transmission fluid specifically developed for manual transmissions of passenger cars and vans.
- A multifunctional MTF which can be used in both manual transmissions and robotic semi-automatic transmissions from the most diverse car brands.

Exceeds the following performance requirements:

- BMW MTF LT-2 / LT-3 / LT-4
- Fiat 9.55550-MZ1 / MZ6 / MZ7
- Ford WSD-M2C200-C / WSS-M2C200-D2 / ESD-M2C186-A
- GM GMW16612 / 1940004 / 19259104
- GM 1940182 / 1940764 / 1940768
- Honda MTF / MTF-II / MTF-III MB 235.10
- Nissan MT-XZ / MT-XZ TL (JR Type)
- PSA B71 2310 / 2315 / 2316 / 2330
- Renault DC4 / DW5
- Special gear oil, MTF 94 Tranself NFJ/NFP/NFX/TRJ/TRP/TRT/TRX/TRZ
- Volvo 97308 / 97309
- VW G 009 317 / 052 171 / 052 178 / 052 512
- VW G 052 527 / 052 549 / 052 726 VW G 50 / 055 512 / 060 726 / 070 726







# Better engine oils Power to perform.



### **TYPICAL ANALYSIS:**

Density at 15 °C, kg/l	0,866
Viscosity 40 °C, mm <sup>2</sup> /s	54,40
Viscosity 100 °C, mm <sup>2</sup> /s	9,46
Viscosity Index	158
Flash Point COC, °C	222
Pour Point, °C	-45
Total Base Number, mgKOH/g	8,7



