

## Better engine oils Power to protect. Power to perform.



## **TOP MTF 75W**

**PRODUCT CODE: T070261** 

**TOP MTF 75W** a fully synthetic low-viscosity manual transmission fluid that can be used in a wide variety of modern vehicles. It is formulated using carefully selected synthetic basestocks and specialised advanced additives, designed to protect transmission systems and offer the best possible fuel economy in all driving conditions.

## **BENEFITS:**

- Multi-vehicle fluid specified by many manufacturers.
- Excellent fuel economy properties
- Outstanding performance across a wide temperature range
- Long-lasting formulation, designed for maximum product life.
- Suitable for synchronised manual transmissions where a fluid of this type is specified by the vehicle manufacturer. It may also be used in some dryclutch DCT systems where a fluid of this type is specified.

Exceeds the following performance requirements:

- API GL-4
- BMW MTF LT-3
- FORD M2C200D-2, M2C200D-3
- PSA SPECIAL PSA FLUID, PART NO. 1618078480 9730A8
- VW G 052 178, G 052 512, G 052 527 G 052 726, G 060 726, G 070 726

## TYPICAL ANALYSIS:

Density @ 20°C	0.840
Kinematic Viscosity @ 100°C (cSt)	6.5
Kinematic Viscosity @ 40°C (cSt)	33.5
Viscosity Index	151
Pour Point (°C)	-45



