

# Better engine oils Power to protect. Power to perform.



# **TOP MTF LV**

**PRODUCT CODE: TO3000** 

**TOP MTF LV** is a fully synthetic ultra low viscosity manual transmission fluid that can be used in a wide variety of modern passenger cars and light duty commercial vehicles. It is formulated using carefully selected synthetic basestocks and specialised advanced additives designed to protect transmission systems and offer the best possible fuel economy in all driving conditions.

#### **BENEFITS:**

- Exceptional low temperature fluidity
- Excellent fuel economy properties
- Outstanding oxidation stability
- Compatible with sensitive materials
- Recommended for use in manual transmissions where an ultra low viscosity fluid is required by the vehicle manufacturer. It may also be used in some dry clutch DCT systems.

### Exceeds the following performance requirements:

- API GL-4
- BMW MTF LT-3
- FIAT 9.55550-MZ6
- FORD M2C200-D2, M2C200-D3, M2C200-E1
- GM 19259104, 19259105, 1940004
- NISSAN SPECIAL GEAR OIL NISSAN LV MT-1
- PSA SPECIAL PSA FLUID PART NO. 1618078480, SPECIAL PSA GEAR OIL 9730 A8
- VW G 052 171, G 052 178, G 052 512, G 052 527, G 052 726, G 052 798, G 055 512, G 060 726

## **TYPICAL ANALYSIS:**

| Density @ 20°C                    | 0.837 |
|-----------------------------------|-------|
| Kinematic Viscosity @ 100°C (cSt) | 6.7   |
| Kinematic Viscosity @ 40°C (cSt)  | 33.0  |
| Viscosity Index                   | 165   |
| Pour Point (°C)                   | -51   |



