

Better engine oils Power to protect. Power to perform.



TOP MILKING MACHINE OIL

PRODUCT CODE: TOMM

TOP MILKING MACHINE OIL is manufactured from highly refined base stocks which possess good oxidation resistance and thermal stability. Fortified with carefully selected additives to further improve performance characteristics including anti-corrosion to protect the system should water be present, anti-wear to reduce wear in pumps used in hydraulic systems, antioxidants and antifoam.

BENEFITS:

- Incorporates inhibitors for protection against all forms of corrosion
- Good anti-foaming and air release properties
- Good demulsification characteristics
- Excellent anti-wear performance
- High oxidation resistance and thermal stability
- Suitable for the majority of hose materials

Suitable for a wide variety of applications. These include industrial hydraulic systems, agricultural and plant equipment, mobile units such as jacks, lightly loaded gears and many others.

Exceeds the following performance requirements:

- Din 51524 Part 2, Category HLP
- ISO 6743/4, Category HM
- Denison HF-2, TP-02100 Filterability Test
- Sperry Vickers M-2950-S, I-286-S
- Afnor NF E 48-600
- Thyssen TH N-256132
- US Steel 127
- SEB 181.222
- **VDMA 24318**

TYPICAL ANALYSIS:

Product Code	томм
Specific Gravity @ 15.6°C	0.88
Kinematic Viscosity @ 40°C (cSt)	68.0
Kinematic Viscosity @ 100°C (cSt)	8.75
Viscosity Index	100
Flash Point (COC °C)	224
Pour Point (°C)	-31





