

Better engine oils Power to protect. Power to perform.



TOP PERFORMANCE CX 5W30

PRODUCT CODE: TO1230

TOP PERFORMANCE CX 5w30 is a high performance universal mid SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger car and light vans with or without turbocharger. Is developed for use in engine which are equipped with or without an exhaust gas after treatment system. Based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

BENEFITS:

- Good thermal and oxidation stability
- mid SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.
- Excellent detergency and dispersency properties.

Exceeds the following performance requirements:

Meets: ACEA C2 / C3

API: SN

- VW 502.00/505.01
- PSA B71 2290
- Dexos[™]2
- BMW LL-04
- Mercedes 229.51, 229.52.
- Opel/Vauxhall OV 040 1547-D30, G30

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m³	ASTM D4052	854
Kin. Viscosity @40°C	mm²/s	ASTM D7042	68
Kin. Viscosity @100°C	mm²/s	ASTM D7042	11.8
Viscosity Index		ASTM D2270	172

North West Business Park, Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Sales@Falzol.ie









Better engine oils





Power to protect. Power to perform.

Viscosity CCS -30°C, max	сР	ASTM D5293	5800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	7.5
Sulphated Ash	%Wt	ASTM D874	0.78



