

Power to protect. Power to perform.



TOP PERFORMANCE EFE 5W20

PRODUCT CODE: TO1202

TOP PERFORMANCE EFE 5W20 A Low viscosity addition to range of premium FULLY SYNTHETIC engine oils. It is formulated using the highest quality synthetic base stocks together with state of the art additive chemistry and is approved to Ford specification WSS-M2C948-B.

TOP PERFORMANCE EFE 5W20 Provides significant fuel saving benefits to the motorist by virtue of its low viscosity and low friction technology while maintaining maximum engine protection and component durability. Exhibits outstanding thermal and oxidative stability and excellent protection against corrosion and black sludge.

BENEFITS:

- Provides significant reductions in fuel consumption
- High thermal stability
- Superior oxidative stability
- Outstanding wear protection
- Excellent low temperature fluidity
- High level of shear stability

Exceeds the following performance requirements:

- ACEA C5
- API SN-RC, SN/CF
- ILSAC GF-5
- Ford WSS-M2C948-B WSS-M2C925-B
- Jaguar Land Rover STJLR.03.5004
- Chrysler MS 6395
- Formulated for use in Ford EcoBoost petrol engines.
- In addition, it is strongly recommended for use in petrol engines for which the specifications WSS-M2C913-B or WSS-M2C913-C were originally prescribed.
- It can also be used where an SAE 5W-20 meeting the following specifications is called for.







Power to protect. Power to perform.



TYPICAL ANALYSIS:

Kinematic Viscosity @ 100°C (cSt)	7.95
Kinematic Viscosity @ 40°C (cSt)	42.5
Viscosity Index	161
Flash Point (Closed) (°C)	200
TBN (mg KOH/g)	8.1
Sulphated Ash (% wt)	0.78
Pour Point (°C)	-36



