

## Better engine oils Power to protect. Power to perform.



### TOP PERFORMANCE GVX 5W30

**PRODUCT CODE: TO1205** 

TOP PERFORMANCE GVX 5W30 is a fuel conserving high performance LOW SAPS engine oil based on 100% synthetic technology for gasoline- and diesel engines of passenger cars and light vans specially designed for the latest generation modern vehicles. Is formulated with synthetic base oil in combination with a special selected additive package to ensure the following properties:

#### **BENEFITS:**

- Excellent thermal and oxidation stability.
- Excellent cold temperature properties for an easy cold start.
- Very good dispersant and detergent properties.
- Fuel saving properties due to low friction properties.
- Very good antifoam, anti-wear and anti-corrosion properties.
- LOW SAPS technology, suitable for engines equipped with exhaust gas after treatment like DPF.
- Long oil change interval possible.

Exceeds the following performance requirements:

- ACEA C3
- MB 229.51 BMW LL-04
- VW 504.00/507.00
- Porsche C30
- API SN-CF

#### **TYPICAL ANALYSIS:**

| Properties                | Unit  | Method     | Typical Value |
|---------------------------|-------|------------|---------------|
|                           |       |            |               |
| SAE Grade                 |       | SAE J3000  | 5W-30         |
| Density @15°C             | kg/m³ | ASTM D4052 | 854           |
| Kin. Viscosity @40°C      | mm²/s | ASTM D7042 | 68            |
| Kin. Viscosity @100°C     | mm²/s | ASTM D7042 | 11.7          |
| Viscosity Index           |       | ASTM D2270 | 165           |
| Viscosity CCS @-30°, max. | сР    | ASTM D5293 | 6600          |
| Flash Point COC           | °C    | ASTM D92   | >201          |
| Pour Point                | °C    | ASTM D7346 | -39           |

Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Sales@Falzol.ie









# Better engine oils Power to perform.



| Total Base Number | mgKOH/g | ASTM D2896 | 7.5  |
|-------------------|---------|------------|------|
| Sulphated Ash     | %Wt     | ASTM D874  | 0.80 |



