



Better engine oils 
Power to protect. Power to perform.



TOP PERFORMANCE GX 0W/40

PRODUCT CODE: TO1252

TOP PERFORMANCE GX 0W/40 the most advanced high performance synthetic passenger car motor oils exclusively developed for latest generation passenger cars and light duty vehicles. The latest formulation technology used in this oil provides unmatched levels of overall lubrication for all types of vehicles, especially high output, turbocharged, supercharged multi valve fuel injected engines in passenger cars, SUVs, light vans & trucks. It is specially designed to ensure maximum protection over extended oil-change intervals. It exceeds the requirements of virtually all the major global OEMs and industry standards.

BENEFITS:

- Outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended drain intervals & engine life.
- Superior antiwear technology provides exceptional wear protection under all conditions.
- Excellent low volatility characteristics reduce oil consumption & hydro-carbon pollution.
- Active cleaning agents ensure maximum engine cleanliness.
- Enhanced frictional properties result in fuel savings.
- Excellent low temperature properties lead to quick cold start and ensure wear protection at start-up.
- Recommended for all latest, high-performance gasoline and diesel engines in cars, SUVs, light vans & trucks, particularly those using recent technologies (multi-valve engines, turbo compressors, and high cylinder capacity) and the new direct injection diesel engines with or without common rail.
- Especially suited to city stop-and-go, heavy load and/or high-speed applications where the conventional oils fail to perform and where such quality oils are recommended.

Exceeds the following performance requirements:

- ACEA A3/B4,
- RN 0700,
- BMW Longlife-01,
- Porsche A40,
- DAIMLER MB 226.5,
- Renault RN0710,
- API SN,

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Sales@Falzol.ie





Better engine oils
Power to protect. Power to perform.



- MB 229.5,
- VW 502 00, 505 00.

TYPICAL ANALYSIS:

Test Parameters	ASTM Method	Typical Values			
Viscosity @ 100 °C, cSt	D 445	12.3	13.4	11.20	14.2
Viscosity Index	D 2270	178	180	178	168
Flash Point, °C	D 92	228	231	234	230
Pour Point, °C	D 97	-39	-39	-36	-36
TBN, mg KOH/g	D 2896	10.1	10.1	10.80	10.5
Density @ 15°C, Kg/l	D 1298	0.845	0.845	0.861	0.857
Sulphated Ash, %wt	D 874	1.09	1.09	1.27	1.29