



**Better engine oils**   
Power to protect. Power to perform.



## TOP PERFORMANCE GX 5W/40

**PRODUCT CODE: T069415**

**TOP PERFORMANCE GX 5W/40** A fully synthetic and mid SAPS engine oil formulated for use with petrol and diesel engines, particularly developed for BMW, GM, Mercedes-Benz and VW vehicles with exhaust after-treatment devices and Pumpe Düse (PD) diesel injection systems. Our specialist Adaptive Molecular Technology maintains engine power, maximises efficiency and improves reliability, ensuring optimum performance in all driving conditions.

### BENEFITS:

- Advanced anti-wear technology helps to protect engine components.
- Engineered to have good oxidation resistance and superb thermal stability. Excellent high and low temperature performance.
- High standards of engine cleanliness.
- Maintains performance over extended drain intervals.
- Provides engine protection under high performance demands.
- Suitable for engines fitted with Pumpe Düse (PD) fuel injection systems.

Exceeds the following performance requirements:

- ACEA C3
- API SN/CF
- BMW LL-04
- Fiat 9.55535-S2
- Ford WSS-M2C917-A
- GM dexos2™
- Mercedes-Benz 229.51/229.31
- Porsche A40
- VW 505.01 (VW Pumpe Düse, PD engines)

### TYPICAL ANALYSIS:

Test Parameters	ASTM Method	Typical Values			
Viscosity @ 100 °C, cSt	D 445	12.3	13.4	11.20	14.2
Viscosity Index	D 2270	178	180	178	168
Flash Point, °C	D 92	228	231	234	230
Pour Point, °C	D 97	-39	-39	-36	-36
TBN, mg KOH/g	D 2896	10.1	10.1	10.80	10.5
Density @ 15°C, Kg/l	D 1298	0.845	0.845	0.861	0.857
Sulphated Ash, %wt	D 874	1.09	1.09	1.27	1.29