



Better engine oils

Power to protect. Power to perform.



TOP SDX 40

TOP SDX 40 A range of quality monograde engine oils, manufactured from high quality mineral base oils and meticulously sourced additives. Provides protection from wear, corrosion and oxidation in turbo charged and naturally aspirated engines, where a monograde oil is specified.

BENEFITS:

- Suitable for turbo charged and naturally asperated petrol & diesel engines.
- Powerful detergent/dispersant additive technology.
- Protection against wear and corrosion.
- SAE 10W, 20W and 30 are suitable for transmission and hydraulic systems in off-highway uses.
- SAE 30, 40 and 50 are suitable for use in petrol and diesel engines where this type of oil is specified. .SAE 50 where specified is suitable for use in gearboxes.

Exceeds the following performance requirements:

- API SG/CF-4
- Caterpillar TO-2
- MAN 270 ZF TE-
- ML 02H, 04B

TYPICAL ANALYSIS:

Density @ 15°C	ASTM D4052	0.88
Flash Point (°C)	ASTM D92	>225
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	134
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	13.9
Pour Point (°C)	ASTM D97	<-15
Total Base Number (mg KOH/g)	ASTM D2896	8.4
Viscosity Index	ASTM D2207	100