



# Better engine oils

Power to protect. Power to perform.



## TOP SS-5 75W-90 LS

**TOP SS-5 75W-90 LS** A semi synthetic gear oil manufactured from a blend of high quality base oils and sophisticated additive technology to withstand high loads in limited slip differentials. Advanced friction modifiers help to reduce chatter and improve traction to provide a longer service life.

### BENEFITS:

- Exceptional shear and thermal stability
- Excellent oxidation stability to provide resistance to aging.
- Helps to reduce differential noise and chatter.
- Long drain intervals.
- Superb protection against rust and corrosion.
- Outstanding load carrying capacity.

Exceeds the following performance requirements:

- API GL-5 LS
- ZF TE-ML 05D, 21C
- Designed for limited slip differentials but can also be used in conventional differential applications where an API GL-5 75W-90 or 80W90 is required.

### TYPICAL ANALYSIS:

Density @	15°C (kg/m <sup>3</sup> ) ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	95
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	15
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	166

