

Better engine oils



PRODUCT CODE: T01730

TOP SUPER TRACTOR OIL UNIVERSAL 10W/40 SS for

agriculture and earth moving equipment. A high quality universal semi-synthetic based oil developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particle Filter (DPF). Formulated on severely hydrocracked base stocks in combination with an unique additive package to reach the following properties.

BENEFITS:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

Exceeds the following performance criteria:

- Engine Spec API CG-4/CF-4/CE/SF MB 228.1 ACEA E3
- JD J20C, J27 Ford M2C86B, 134D
- Ford M2C159B Case MS 1204, 6, 7, 9 MF M 1135/1139/1143/1144/1145
- CAT TO-2 API GL-4
- Allison C4 ZF TE-ML 06A, 06B, 06C, 06D, 06E, 06H 07B NH 82009201, 2,
- Eaton M-2950S Eaton I-280-S Danfoss

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m ³	ASTM D4052	861
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	157
Viscosity CCS @-25°, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	10.6

