



Better engine oils 
Power to protect. Power to perform.



TOP SUPERFLEET SUPREME 15W40

PRODUCT CODE TO1540

TOP SUPERFLEET SUPREME 15W40 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. Is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

BENEFITS:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

Exceeds the following performance requirements:

- MB-Approval 228.3
- MAN M 3275
- Volvo VDS-3
- Renault RLD-2
- Mack EO-M
- Scania LDF-2
- API CI-4
- ACEA E7
- DDC 93K215
- Caterpillar ECF-1a, ECF-2
- Global DHD-1 JASO DH-1
- Allison C4 MTU Type 2
- Mack EO-M+ Cummins CES 20077/20078
- DAF HP2

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie



JASO



Better engine oils
Power to protect. Power to perform.



TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	15W-40
Density @15°C	kg/m ³	ASTM D4052	880
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	101
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.0
Viscosity Index		ASTM D2270	143
Viscosity CCS @-20°, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	10.4
Sulphated Ash	%Wt	ASTM D874	1.5

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie

