



**Better engine oils**   
Power to protect. Power to perform.



## TOP SUPERFLEET ULD 10W/40

**PRODUCT CODE:TO1523**

**TOP SUPERFLEET ULD 10W/40** An advanced heavy duty diesel engine oil manufactured from superior quality synthetic base oils. Incorporating specialist Adaptive Molecular Technology that has been combined with low ash technology to optimise the power and efficiency of your vehicle to help maintain peak reliability to ensure maximum performance and emission compliance.

### BENEFITS:

- Excellent stability offering consistent long-term performance.
- Extended drain capabilities.
- Increased protection against wear and corrosion.
- Low volatility providing reduced oil consumption and emissions Maintains very high standards of engine cleanliness.
- Superb levels of resistance against the effects of biofuel.

Exceeds the following performance criteria.

- ACEA E4/E7 (E5)
- API CI-4
- Cummins 20078, 20077
- Deutz DQC IV-10
- Mack EO-N MAN M3275, M3277
- Mercedes-Benz 228.5, 228.3
- Renault RXD
- Scania LDF-3
- Volvo VDS-3
- Suitable for a range of normally aspirated and turbocharged heavy-duty diesel engines in trucks, buses, plant and industrial equipment over extended drain intervals.

### TYPICAL ANALYSIS:

Density @ 15°C	ASTM D4052	0.867
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )	ASTM D445	101.2
Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> )	ASTM D445	14.2
Pour Point (°C)	ASTM D97	-36
Total Base Number (mg KOH/g)	ASTM D2896	12
Viscosity Index	ASTM D2207	145

Northwest Business Park Collooney, Co Sligo, Ireland  
Tel: 071-9130033 Email: Info@Falzol.ie



JASO