

SUPERFLEET XLE LOW SAPS 10W40

PRODUCT CODE: T01530

SUPERFLEET XLE LOW SAPS 10W40 An advanced heavy duty diesel engine oil manufactured from superior quality synthetic base oils. Incorporating our specialist Adaptive Molecular Technology that has been combined with low ash technology to optimise the power and efficiency of your vehicle to help maintain peak reliability to ensure maximum performance and emission compliance.

BENEFITS:

- Excellent stability offering consistent long-term performance.
- Extended drain capabilities. Increased protection against wear and corrosion.
- Low volatility providing reduced oil consumption and emissions
- Suitable for engines with or without exhaust aftertreatment devices.
- Very high levels of engine cleanliness.

Exceeds the following performance requirements:

- ACEA E6/E9 (E7) API CJ-4
- Cummins 20081
- Deutz DQC IV-10 LA
- JASO DH-2
- Mack EO-O Premium Plus
- MAN M3575, M3477
- Mercedes-Benz 228.51, 228.31
- Renault RLD-3, RGD
- Scania Low Ash
- Volvo VDS-4, VDS-3
- Suitable for DAF Suitable to use for inter-city or long-haul heavy duty diesel engines in commercial, plant, buses and industrial equipment.

TYPICAL ANALYSIS:

Density @ 15°C	ASTM D4052	0.869
Flash Point (°C)	ASTM D92	210
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	93
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	13.9
Pour Point (°C)	ASTM D97	-36
Total Base Number (mg KOH/g)	ASTM D2896	10
Viscosity Index	ASTM D2207	154

Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Info@Falzol.ie

