



Better engine oils

Power to protect. Power to perform.



TOP SYNGEAR 75W - 140

PRODUCT CODE: TO2381

TOP SYNGEAR 75W – 140 is a fuel saving universal high performance EP gear oil based on synthetic technology for use as total driveline gear of passenger cars, vans, light- and heavy commercial vehicles requiring a GL-4/GL-5 performance. Formulated with synthetic base stocks in combination with a unique EP-additive technology to achieve the following performance:

BENEFITS:

- Very good protection against wear.
- Very good performance against the forming of foam and corrosion.
- Outstanding Oxidation- and thermal stability.
- Superior seal compatibility
- Fully compatible with synchromesh transmissions.

Exceeds the following performance requirements:

- API GL-4/GL-5
- API MT-1
- MIL-PRF-2105E
- SAE J2360
- MAN 342-M3 MAN 341-Z2 MAN 341 E3 RVI B0032/2-3
- MB 235.8
- Scania STO 1:0
- Arvin Meritor O-76-N
- MACK GO-J
- MAN M 3343S
- DAF IVECO ZF TE-ML 02B/05B/07A/12B/12L/12N/16F/17B/19C/21
-

TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W-140
Density @15°C	kg/m ³	ASTM D4052	869
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	168
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	25
Viscosity Index		ASTM D2270	>150
Viscosity Brookfield @-40°C	cP	ASTM D5293	150000
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-48

Northwest Business Park Collooney, Co Sligo, Ireland
Tel: 071-9130033 Email: Info@Falzol.ie

