

Better engine oils Power to protect. Power to perform.



TOP SYNGEAR 75W 90

PRODUCT CODE: TO2380

TOP SYNGEAR 75W 90 A high-performance fully synthetic gear oil manufactured from a blend of synthetic oil, sheer stable viscosity index improvers and a multipurpose extreme pressure additive system. It offers a high level of performance when compared to straight mineral oil whilst being compatible with mineral oils which enables it to be simply used as a replacement product on a drain and fill basis.

BENEFITS:

- Exceptional shear and thermal stability.
- Excellent oxidation stability to provide resistance to aging.
- Long drain intervals.
- Superb protection against rust and corrosion.
- Outstanding load carrying capacity.

Exceeds the following performance requirements:

- API GL-4, GL-5, MT-1
- MAN M3343 Type S
- Mack GO-J
- Mercedes-Benz 235.8
- MIL-PRF-2105E
- SAE J2360
- Scania STO 1:0
- Volvo 97312
- ZF TE-ML 02B, 05A, 07A, 08, 16B, 17B, 21A

TYPICAL ANALYSIS:

Density @ 15°C (kg/m3)	ASTM D4052	0.85
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s²)	ASTM D445	100
Kinematic Viscosity @ 100°C (mm/s²)	ASTM D445	16.2
Pour Point (°C)	ASTM D97	<-41
Viscosity Index	ASTM D2207	175







Better engine oils





Power to protect. Power to perform.

Northwest Business Park Collooney, Co Sligo, Ireland Tel: 071-9130033 Email: Info@Falzol.ie



