



# Better engine oils

Power to protect. Power to perform.



## TOP TRANSFLUID MULTI G 10W/30

**PRODUCT CODE: TO1750**

**TOP TRANSFLUID MULTI G 10W/30** A premium universal transmission and hydraulic fluid, specifically designed for use in agricultural power transmissions, hydraulics and rear axles including oil immersed wet brakes. Using high quality base oils and exceptional additive technology to provide an advanced lubricant which demonstrates excellent performance characteristics against various stringent test requirements of major equipment manufacturers.

### **BENEFITS:**

- Allows for rationalisation of products. Good resistance against aeration & foaming.
- Engineered to have good oxidation resistance, thermal stability & superb low temperature performance.
- Excellent brake squawk & chatter suppression. Exceptional anti-wear properties.
- Provides constant frictional performance.
- Suitable to use where API GL-4 SAE 10W-30 or SAE 80W is required.

Exceeds the following performance criteria:

- API GL-4
- AGCO/Allis 821 XL
- Allison C4
- Case MS 1204/1206/1207
- Case New Holland MAT 3525
- Caterpillar TO-2
- Denison HF-0/1/2
- Ford M2C86-B/C, M2C134-D
- John Deere J20C
- Komatsu AXO 80
- Kubota UDT
- Massey Ferguson M1127A, M1135, M1143, M1145
- New Holland 410B
- Sperry Vickers M-230-S, M-2950-S, I-280-S
- Volvo WB101
- ZF TE-ML 03E, 05F, 06K, 17E, 21F

Northwest Business Park Collooney, Co Sligo, Ireland  
Tel: 071-9130033



JASO



# Better engine oils



Power to protect. Power to perform.



## TYPICAL ANALYSIS:

Appearance		Clear & bright, red
Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.868
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )	ASTM D445	69
Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> )	ASTM D445	10.7
Pour Point (°C)	ASTM D97	-35
Viscosity Index	ASTM D2207	144

Northwest Business Park Collooney, Co Sligo, Ireland  
Tel: 071-9130033



JASO