



# Better engine oils

Power to protect. Power to perform.



## TOP ULTRA 2T PLUS

**PRODUCT CODE:TO1910**

**TOP ULTRA 2T PLUS** is a high quality semi-synthetic lubricant specially developed for high powered 2-stroke air cooled gasoline engines fitted with oil-injection or premix systems. Is based on a high quality virgin and synthetic base oils in combination with a special selected additive package to obtain the following properties:

### BENEFITS:

- Outstanding protection against piston scuffing and premature wear of engine components.
- Excellent control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Low ash additive technology prevents pre-ignition and spark plug fouling.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures.

Exceeds the following performance requirements:

- API TC
- JASO FD
- ISO-L-EGD

### TYPICAL ANALYSIS:

Properties	Unit	Method	Typical Value
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	872
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D445	69
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D445	9.5
Viscosity Index		ASTM D2270	123
Flash Point COC	°C	ASTM D92	85
Pour Point	°C	ASTM D97	-33
Total Base Number	mgKOH/g	ASTM D2896	1.4
Sulphated Ash	%Wt	ASTM D78	0.14