



ROCK BREAKER GREASE

ROCK BREAKER GREASE is specially developed using a blend of semi-synthetic base oil manufactured with a high temperature thickener containing a high level of graphite to extend lubrication periods. It is designed particularly for hydraulic hammer lubrication, pin and bush type of applications on large earth moving and general off-road heavy plant machinery. Is enhanced by the addition of laminar lubricating solids, and its adhesive properties resist water wash off. This product has also found use in the lubrication of open gears. Can be applied manually, or by using a standard grease gun (400gm cartridges available). As with all greases used for the first time, check compatibility with the grease applied previously and if necessary, purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

BENEFITS:

- High degree of water resistance
- Reduced grease leakage tendency
- Excellent load carrying capability and shock load resistance
- Good sealing properties in dusty conditions
- Inherent adhesive nature

TYPICAL ANALYSIS:

Properties	Specification	Results
Appearance	-	Smooth adhesive Grease
Colour	-	Black
NLGI classification	-	2/3
Thickener	-	Bentone
Base oil	-	Semi Synthetic
Worked penetration	IP50	230-260
Dropping point (°C)	IP132	>260
Oil separation (%)	IP121	N/a
Copper corrosion	IP112	Pass
Resistance to corrosion Emcor (a)	IP 220	N/a
Water washout @ 39°C %	ASTM D1264	2
Four Ball Weld Load (kgs)	IP 239	500
Operating temperature range	-	-5°C to 150°C
Solids %	-	10

Falzol Lubricants,
Northwest Business Park, Collooney, County Sligo,
Ireland Telephone: +353 (0)71 91 30033 sales@falzol.ie www.falzol.ie

