



# Better engine oils

Power to protect. Power to perform.



## TOP GEAR OIL LS 85W/140

**PRODUCT CODE: TO1120**

**TOP GEAR OIL LS 85W/140** A gear oil manufactured from high quality base oils blended with advanced friction modifiers and extreme pressure technology. Designed especially for heavily loaded limited slip differentials to reduce noise, chatter and improve traction to provide longer service intervals in heavy duty vehicles, off-highway plant and agricultural machinery.

### BENEFITS:

- Excellent compatibility with seals & friction-disk materials.
- Exceptional oxidation stability for long service intervals.
- Superior load carrying capability.
- Superb low and high temperature performance.
- Reduced noise, chatter and vibrations under intensive use.
- Very high levels of rust and corrosion resistance.

Exceeds the following performance requirements:

- API GL-5 LS
- Mack GO-H
- MIL-L-2105D
- ZF TE-ML 05C, 12C Benefits
- Suitable to use in standard differentials, axles and reduction hubs where an API GL-5 SAE 85W-140 gear oil is required.

### TYPICAL ANALYSIS:

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.90
Flash Point (°C)	ASTM D92	>220
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	350
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	26
Pour Point (°C)	ASTM D97	<-15
Viscosity Index	ASTM D2207	98

Northwest Business Park Collooney, Co Sligo, Ireland  
Tel: 071-9130033 Email: Info@Falzol.ie



JASO