



Better engine oils
Power to protect. Power to perform.



TOP COMPRESS OIL 46

TOP COMPRESS OIL 46 Blended from carefully selected base oils and high performance additive technology for extended 4000hrs service intervals. Specially designed to have a very low tendency to form carbon whilst being fortified to inhibit wear, corrosion, oxidation and foaming.

BENEFITS:

- Demulsifying to ensure rapid water separation.
- Excellent anti-wear characteristics.
- Good anti-foam and air release properties.
- Outstanding corrosion protection.
- Superior oxidation resistance to provide a long service life

Exceeds the following performance criteria:

- ANFOR NF E 48-603 BS 489
- Cincinnati P55
- Dennison HF-0
- DIN 51354 Stage 11
- DIN 51506 VD-L
- DIN 51524 Part II DP 6521 DAA/DAB/DAG/DAH

TYPICAL ANALYSIS

Appearance		Straw/light amber liquid
Density @ 15°C (kg/m3)	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	46
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	6.8
Pour Point (°C)	ASTM D97	<-25
Viscosity Index	ASTM D2207	101
Copper Corrosion	ASTM D130 A&B	Pass
Demulsibility	ASTM D1401	40-40-0
Oxidation	ASTM D943	4000hrs

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.